

- UCC-3HD05B-U3
- UCC-3HD10S-U3
- UCC-3HD10B-U3

KEY FEATURES



- Resolution: up to 1080p60
- Zoom: Optical 5X, 10X
- Horizontal Angle of View: 81°, 67°, 48° Optional.
- Video Output: USB3.0, HDMI
- Supports UVC1.5, UAC2.0, Virtual COM port
- Use with Familiar UC Software Video Applications
- Built in USB Hub to use compatible third party USB devices.

DESIGN



- Compact and contemporary design, use for Huddle Space and Mid-Size or smaller conference room.
- Camera is integrated with quiet pan and tilt Stepper Motor to ensure accuracy, smoothness and speed in control.
- Use with popular UC Video Applications. Works with popular cloud based video conferencing software or APPs.
- Built in USB Hub to support USB Mic or speaker and other compatible devices.

FUNCTIONALITY

- Ideal for Huddle Space to Mid-Size video-conferencing, video communication Plug-N-Play
- HDMI provides additional local video output.
- Virtual COMM Port available for third party system integration.
- 128 (Speed:200°/s, 6 presets on remote controller), Preset speed adjustable: 0-5 level
- Horizontal:±340 degrees continuous pan (Speed Adjustable 0.05°- 100°/s)
- Built-in Mic
- Control: USB3.0, PC-UI via Virtual COMM Port, IR Controller.
- Standard mounting and ceiling mounting with E-Flip function.
- New designed remote controller provides user friendly operation.



IR Remote Controller



Product Specification

Model No.	UCC-3HD05B-U3	UCC-3HD10B-U3	UCC-3HD10S-U3
Camera	5X-B	10X-B	10X-S
Image Sensor	1/2.8 inch CMOS 2.0MP	1/2.86inch CMOS 2.2MP	1/2.8inch CMOS 2.14MP
Lens	Optical 5X, 3.1~15.5mm	Optical 10X, 6.53~62.18mm	Optical 10X, 3.8~38mm
Digital Zoom	12X	12X	12X
Horizontal Angle of View	83.9°(W)~20.4°(T)	48°(W)~4.9°(T)	67°(W)~7.6°(T)
Aperture	F1.6(W)~F2.8(T)	F1.8(W)~F2.5(T)	F1.8(W)~F3.4(T)
Min. Illumination	0.5 lux(F1.8,IRC Close), 0.1 lux(F1.8, IRC Open)	0.2 lux(F1.8,IRC Close), 0.005 lux(F1.8, IRC Open)	Color: 1.4 lx (F1.8, AGC on, 1/30 s) High Sensitivity Mode Color: 0.35 lx (F1.8, AGC on, 1/30 s)
Shutter Speed	1/1~1/10000s		
Focus	Auto,Push.Manual		
White Balance	Auto, Manual		
Exposure	Auto,Manual,Shutter/Iris Priority Mode		
Day/Night/Auto ICR	YES		
Backlight Compensation	YES		
WDR	YES		
Privacy Zone Masking	-		
Noise Reduction	2D/3D		
S/N Ratio	≥50db		
Image Stabilization	NO		
Image Flipper	YES		
OSD	YES		
Mechanical			
Pan Movement	Horizontal:±350 degrees continuous pan (Zoom Adaptive Speed Range: 0.05°~100°/S)		
Tilt Movement	Vertical:+90 degrees to -30 degrees (Zoom Adaptive Speed Range: 0.05°~72°/S)		
Preset Position	128 (Speed adjustable: Up to 200°/S, 6 presets on remote controller.) 0~5 Level Adjustable		
Home Position	Support		
Environment	Indoor		
Interface			
Video Output	USB3.0 ,HDMI		
Video Format	1080p:60/50/30/25; 720p:60/50/30/25		
USB Interface	1XUSB3.0 (Type B), built-in extra USB Hub 1XUSB3.0 (Type A)		
Audio I/O	Built-in Mic		
Control Interface	IR Remote Controller, Virtual COMM Port, UVC1.5		
Compatible Integration	USB3.0, UVC1.5 & UAC2.0		
General			
Operating Temperature	-10 to +50 (°C)		
Operating Humidity	≤80% Suitable for Use		
Power Input	DC12V		
Power Consumption	12W		
Dimension	138x162mm		
Weight	1.28kg		

ORDER INFORMATION

- UCC-3HD10S-U3
- UCC-3HD10B-U3
- UCC-3HD05B-U3